

### REBAR Designations

| Description of product              | Obsolete Bar Designation | AS4671 Designation | Abbreviated Designation |
|-------------------------------------|--------------------------|--------------------|-------------------------|
| Hot rolled ribbed rebar             | 400Y_ = Y_               | D500N_             | N_                      |
| Hot rolled ribbed rebar (POOLSTEEL) | 250S_ = S_               | D250N_             | S_                      |
| Hot rolled plain round              | 250R_ = R_               | R250N_             | R_                      |
| Cold drawn round wire               | W_                       | R500L_             | W_                      |
| Cold rolled ribbed wire             | RW_                      | D500L_             | DW_                     |

**Notes:**

1. ( \_ ) = bar size.
2. Symbols W and S are not referenced in AS4671.

### REOMESH Designations

| Description of mesh | Obsolete Mesh Designation    | AS4671 Designation                               |
|---------------------|------------------------------|--|
| Square mesh         | RF52-RF102<br>(F52-F102)     | SL 52-SL102                                      |
| Rectangular mesh    | RF718-RF1218<br>(F718-F1218) | RL718-RL1218                                     |
| Trench mesh         | RF8TM-RF12TM<br>(F8TM-F12TM) | x-L8TM / x-L12TM<br>eg. 4-L12TM<br>(or L12TM300) |